



TGMi Cabinet Model FS300

General

FModel Free Standing Food Waste Disposer

Capacity 600kg of organic waste per hour

Dimensions (h x w x d)

850/865mm x 400mm x 600mm

Electrical information

Motor 1.1kW (1.5 HP) standard power*

Voltages 220 – 1 – 50/60 400/440 – 3 -50/60

Fuse rating 16A - 3 phase

Operator controls IP65 mounted in front plate

Motor on and off button

Installation information

Water connection 15/22mm connection.

Minimum pressure (head) of 0.4 bar (4m)

Water consumption 18-25 litres per minute

Waste connection 2" BSP threaded flange for connection to 50mm piping

Electrical connection mains cable (no plug)

Other features

Water control Solenoid valve for automatic water control

Operator safety Metal baffle and time delayed interlock system

Special features Automatic thermal overload to protect the motor

Manually controles or Auto Reverse (option)

Customer option

Class A airbreak

Magnetic cutlery saver

Auto Reverse Switch for extended (double) life cicle of cutting elements

Product order code details

GM68/223 3 phase

Shipping specification (Aprox)

Packing dimensions (h x w x d)

980mm x 480mm x 620mm

Packing volume 0.292m³

Packing weight (gross/net) 73kg/63kg

* 2.2kW on special request